

SAFETY DATA SHEET

2,3,3,3-Tetrafluoroprop-1-ene (R1234yf)

Public reference document issued by EGO INDUSTRIAL GAS SRL as supplier/distributor. It does not state that EGO is the chemical manufacturer. The regulatory SDS must match the supplied product, batch and destination country and is sent to the buyer before dispatch.

Supplier / distributor	EGO INDUSTRIAL GAS SRL
VAT ID	RO45636173
Document ID	EGO-SDS-R1234YF-EN
Issue	1.0 / 15.08.2026
Status	Public reference document

contact@egolog.ro · <https://egolog.ro> · Calea Dârvarilor nr. 178, Sat Goștilele, Oraș Fundulea, Jud. Călărași, România

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : R1234yf SDS identifier: EGO-SDS-R1234YF-EN Other means of identification : 2,3,3,3-Tetrafluoroprop-1-ene; HFC- 1234yf CAS no. : 754-12-1 EC no. : 468-710-7 Index no. : --- REACH no. : 01-0000019665-61 Chemical formula : CHF (CFCF = CH) 3 2 4 3 2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : See the list of identified uses and exposure scenarios in the annex of the safety data sheet. Industrial and professional uses. Perform risk assessment prior to use. Uses advised against : Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet

Supplier / distributor in Romania EGO INDUSTRIAL GAS SRL VAT ID: RO45636173 Calea Dârvarilor nr. 178, Sat Goștilele, Oraș Fundulea, Jud. Călărași, România Website: <https://egolog.ro> Document identifier: EGO-SDS-R1234YF-EN

1.4. Emergency telephone number

European emergency number: 112 (24/7).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Physical hazards Flammable gases, Category 1B H221 Gases under pressure : Liquefied gas H280

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP) : GHS02 GHS04 Signal word (CLP) : Danger R1234yf Hazard statements (CLP) : H221 - Flammable gas. H280 - Contains gas under pressure; may explode if heated. Precautionary statements (CLP) - Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. - Response : P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 - In case of leakage, eliminate all ignition sources. - Storage : P403 - Store in a well-ventilated place. Supplemental information : Contains greenhouse gases listed in Annex I of EU 2024/573.

2.3. Other hazards

Asphyxiant in high concentrations. Contact with liquid may cause cold burns/frostbite. These high concentrations are within the flammability range. Not classified as PBT or vPvB. The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name Product identifier % Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors 2,3,3,3-Tetrafluoroprop-1-ene CAS no.: 754-12-1 ≤ 100 Flam. Gas 1B, H221 (R1234yf, HFC- 1234yf) EC no.: 468-710-7 Press. Gas (Liq.), H280 Index no.: --- REACH no.: 01-0000019665-61 Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Maintain an open airway. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. - Skin contact : Carefully remove contaminated clothing. In case of frostbite spray with water for at least 15 minutes. Do not use hot water! Apply a sterile dressing. Obtain medical assistance. - Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove any contact lenses. Obtain medical assistance. - Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Take first aid measures. Loosen tight clothing, such as a collar, tie or belt. Place the unconscious person in a lateral position. Seek medical attention. R1234yf

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog. Dry powder. Carbon dioxide. Shutting off the source of the gas is the preferred method of control. Be aware of the risk of formation of static electricity with the use of CO extinguishers. Do not use them in places where a flammable atmosphere may be present. - Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode. Hazardous combustion products : Carbon monoxide. Hydrogen fluoride. Carbonyl fluoride.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Move containers away from the fire area if this can be done without risk. Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 469 - Protective clothing for firefighters. Standard EN 659 - Protective gloves for firefighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Act in accordance with local emergency plan. Try to stop release. Evacuate area. Eliminate ignition sources. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment. For emergency responders : Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13. R1234yf

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product : Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Ensure equipment is adequately earthed. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Take precautionary measures against static discharge. Purge air from system before introducing gas. The product must be handled in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke while working with the product. Wash hands after use. Only experienced and properly instructed persons should handle gases under pressure. Wear personal protective equipment (See section 8). Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into work area. Safe handling of the gas receptacle : Refer to supplier's container handling instructions. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If the protection cap is too tight, remove it with adjustable wrench. Never insert sharp objects into the cavities of the cap, this can lead to damage to the valve and leakage. Open valve slowly to avoid pressure shock. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not allow backfeed into the container. Suck back of water into the container must be prevented. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from oxidant gases and other oxidants in store. All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

7.3. Specific end use(s)

None. R1234yf

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,3,3,3-Tetrafluoroprop-1-ene (R1234yf, HFC- 1234yf) (754-12-1) DNEL: Derived no effect level (Workers) Long-term - systemic effects, inhalation 950 mg/m³ 2,3,3,3-Tetrafluoroprop-1-ene (R1234yf, HFC- 1234yf) (754-12-1) PNEC: Predicted no effect concentration Aqua (freshwater) 0.1 mg/l Aquatic, intermittent releases 1 mg/l

8.2. Exposure controls

8.2.1. Appropriate engineering controls Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. 8.2.2. Individual protection measures, e.g. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. • Eye/face protection : Wear goggles when transfilling or breaking transfer connections. Standard EN 166 - Personal eye-protection - specifications. • Skin protection - Hand protection : Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms. Wear cold insulating gloves when transfilling or breaking transfer connections. Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance. - Other : Consider the use of flame resistant anti-static safety clothing. Standard EN ISO 14116 - Limited flame spread materials. Standard EN 1149-5 - Protective clothing: Electrostatic properties. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear. • Respiratory protection : Recommended: Filter AX (brown). Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Gas filters do not protect against oxygen deficiency. Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. • Thermal hazards : None in addition to the above sections. 8.2.3. Environmental exposure controls Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. R1234yf

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance - Physical state at 20°C / 101.3kPa : Gas. - Colour : Colourless. Odour : Ethereal. Melting point / Freezing point : Not applicable for gases and gas mixtures. Boiling point : -29 °C Flammability : Flammable gas. Lower explosion limit : 6.2 vol % Upper explosion limit : 12.3 vol % Flash point : Not applicable for gases and gas mixtures. Auto-ignition temperature : 405 °C Decomposition temperature : Not applicable. pH : Not applicable for gases and gas mixtures. Viscosity, kinematic : Not applicable for gases and gas mixtures. Water solubility [20°C] : 198.2 mg/l Partition coefficient n-octanol/water (Log Kow) : 2.15 Vapour pressure [20°C] : 5800 hPa Vapour pressure [50°C] : 13020 hPa Density and/or relative density : Not applicable for gases and gas mixtures. Relative vapour density (air=1) : Heavier than air. Particle characteristics : Not applicable for gases and gas mixtures. Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes Explosion limits : Not known. Oxidising properties : No oxidising properties. Tci : 6.2 % Critical temperature [°C] : 95 °C 9.2.2. Other safety characteristics Molar mass : 114.04 g/mol Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air. May react violently with oxidants.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid moisture in installation systems. (See Section 7.)

10.5. Incompatible materials

Light metals, alkalis, caustic products, strong oxidisers, finely divided metals (Al, Mg, Zn), moisture. For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. R1234yf

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Classification criteria are not met. 2,3,3,3-Tetrafluoroprop-1-ene (R1234yf, HFC- 1234yf) (754-12-1) LC50 Inhalation - Rat [ppm] 405000 ppm/4h Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Germ cell mutagenicity : No known effects from this product. Carcinogenicity : No known effects from this product. Toxic for reproduction : Fertility : No known effects from this product. Toxic for reproduction : unborn child : No known effects from this product. STOT-single exposure : No known effects from this product. STOT-repeated exposure : No known effects from this product. Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Classification criteria are not met. EC50 48h - Daphnia magna [mg/l] : > 100 mg/l EC50 72h - Algae [mg/l] : > 100 mg/l LC50 96 h - Fish [mg/l] : > 197 mg/l

12.2. Persistence and degradability

Assessment : Not readily biodegradable.

12.3. Bioaccumulative potential

Assessment : Not expected to bioaccumulate due to the low log K (log K < 4). ow ow See Section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Assessment : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : No known effects from this product. Effect on the ozone layer : No effect on the ozone layer. Ozone depletion potential [R11=1] : 0 Global warming potential [CO=1] according to : 0,501 2 Annex I of EU 2024/573 Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect. Contains greenhouse gases listed in Annex I of EU 2024/573. R1234yf

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30/21 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods. Must not be discharged to atmosphere. Return unused product in original container to supplier. List of hazardous waste codes (from Commission : 14 06 01 *: Chlorofluorocarbons, HCFC, HFC. Decision 2000/532/EC as amended) 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN UN-No. : 3161

14.2. UN proper shipping name

Transport by road/rail/inland waterways : LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene (ADR/RID/ADN) (R1234yf, HFC- 1234yf)) Transport by air (ICAO-TI / IATA-DGR) : Liquefied gas, flammable, n.o.s. (2,3,3,3-Tetrafluoroprop-1-ene (R1234yf, HFC- 1234yf)) Transport by sea (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene (R1234yf, HFC- 1234yf))

14.3. Transport hazard class(es)

Labelling :

2.1 : Flammable gases.

Transport by road/rail/inland waterways (ADR/RID/ADN) Class : 2 Classification code : 2F Hazard identification number : 23 Tunnel Restriction : B/D - Tank carriage: Passage forbidden through tunnels of category B, C, D and E. Other carriage: Passage forbidden through tunnels of category D and E
Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s)) : 2.1 Transport by sea (IMDG) Class / Div. (Sub. risk(s)) : 2.1 Emergency Schedule (EmS) - Fire : F-D Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail/inland waterways : Not applicable. (ADR/RID/ADN) Transport by air (ICAO-TI / IATA-DGR) : Not applicable. Transport by sea (IMDG) : Not applicable. R1234yf

14.5. Environmental hazards

Transport by road/rail/inland waterways : None. (ADR/RID/ADN) Transport by air (ICAO-TI / IATA-DGR) : None. Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s) Transport by road/rail/inland waterways : P200. (ADR/RID/ADN) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft : Forbidden. Cargo Aircraft only : 200. Transport by sea (IMDG) : P200. Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation

This document refers to Regulation (EC) No 1907/2006 (REACH), Regulation (EC) No 1272/2008 (CLP), Regulation (EU) 2020/878 and Regulation (EU) 2024/573. National conditions and permitted use must be checked for the actual product and destination country.

15.2. Chemical safety assessment

The applicable assessment is confirmed against the actual product, batch and supplier data before dispatch.

SECTION 16: Other information

EGO issue 1.0 dated 15.08.2026. Public reference document issued by EGO INDUSTRIAL GAS SRL as supplier/distributor. It does not state that EGO is the chemical manufacturer and does not replace the regulatory SDS for the product and batch actually supplied. The current regulatory SDS is sent to the buyer before dispatch. Main abbreviations: ADR, ADN, IMDG, IATA, CLP, REACH, PBT, vPvB, DNEL, PNEC.